

AFTERMARKET AUTO PARTS ALLIANCE, INC
2706 TREBLE CREEK, SUITE 100
SAN ANTONIO, TX, 78258

PRODUCT: AV 7655 ROCKER PANEL PROTECTOR BEIGE

SECTION 01: Chemical product and company identification

Product name..... AV 7655 ROCKER PANEL PROTECTOR BEIGE
Manufactured for..... Aftermarket Auto Parts Alliance, Inc
2706 Treble Creek, Suite 100
San Antonio, TX 78258
24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC) - IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300.
Material use..... Paints.
Chemical family..... Mixture.
Preparation date..... May 21, 2015.
Hazard rate
NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.
HMIS..... H: 2 F: 3 R: 0.

SECTION 02: Hazards identification



Signal Word..... DANGER.
Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Irritant 2. STOT SE 3. Reproductive 2.
STOT RE 2.
Hazard Description..... H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters
airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361 This
product contains ingredients that are suspected of damaging fertility or the unborn child.
H373 May cause damage to the liver and kidneys through prolonged or repeated contact.
Precautionary Statements..... P201 Obtain special instructions before use. P202 Do not handle this product until all
safety instructions have been read and understood. P210 Keep away from heat, sparks,
open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P235
Keep cool. P240 Ground and bond container and receiving equipment. P241 Use
explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary
measures against static discharge. P260 Do not breathe the mist, vapours, or spray. P264
Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280
Wear protective gloves and eye protection.
Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and
follow instructions provided by the centre. P331 Do NOT induce vomiting. P303 + P361 +
P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly
with water and use safety shower. P333 + P313 If skin irritation or rash occurs, get
medical advice/attention. P304 + P340 - If inhaled remove person to fresh air and keep
comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P362 +
P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire
- use dry chemical powder, CO2 or 6% foam to extinguish.
Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool.
P405 Store locked up.
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENTS | CAS # | WT. % |
|--------------------------------|------------|-------|
| ACETIC ACID, TERT-BUTYL ESTER | 540-88-5 | 30-60 |
| TOLUENE | 108-88-3 | 10-30 |
| SBR (STYRENE BUTADIENE RUBBER) | 9003-55-8 | 7-13 |
| HYDROCARBON POLYMER | 9011-11-4 | 5-10 |
| CALCIUM CARBONATE | 1317-65-3 | 1-5 |
| BENTONE | 68953-58-2 | 1-5 |

PRODUCT: AV 7655 ROCKER PANEL PROTECTOR BEIGE**SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS**

| | | |
|--------------------|------------|---------|
| TITANIUM DIOXIDE | 13463-67-7 | 0.1-1.0 |
| CRYSTALLINE SILICA | 14808-60-7 | <0.1 |

SECTION 04: First aid measures

| | |
|-----------------------------|---|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Additional information..... | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: Fire fighting measures

| | |
|---------------------------------------|---|
| Extinguishing media..... | "Alcohol" foam, CO2, dry chemical. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Use cold water spray to cool exposed containers to minimize risk of rupture . |
| Hazardous combustion products..... | Oxides of carbon (CO, CO2). Oxides of nitrogen. |
| Special fire fighting procedures..... | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. |

SECTION 06: Accidental release measures

| | |
|-----------------|---|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). |
|-----------------|---|

SECTION 07: Handling and storage

| | |
|--------------------------|---|
| Handling procedures..... | Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame. |
| Storage needs..... | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. |

SECTION 08: Exposure controls / personal protection

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|-----------------------------------|-----------------|-------------------|-----------------|--------------------|------------------------|-------|
| ACETIC ACID, TERT-BUTYL ESTER | 200 ppm | Not established | 200 ppm | Not established | 200 ppm | |
| TOLUENE | 20 ppm | Not established | 200 ppm | 500 ppm 10 minutes | 100 ppm / STEL 150 ppm | |
| SBR (STYRENE BUTADIENE RUBBER) | Not established | Not established | Not established | Not established | Not established | |
| HYDROCARBON POLYMER | Not established | Not established | Not established | Not established | Not established | |
| CALCIUM CARBONATE | Not established | Not established | 5 mg/m3 | Not established | 5 mg/m3 | |

PRODUCT: AV 7655 ROCKER PANEL PROTECTOR BEIGE
SECTION 08: Exposure controls / personal protection

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|-------------------------------|---|-------------------|-----------------|------------------|-----------------|-----------------|
| BENTONE | Not established | Not established | Not established | Not established | Not established | Not established |
| TITANIUM DIOXIDE | 10 mg/m3 | Not established | 15 mg/m3 | Not established | Not established | Not established |
| CRYSTALLINE SILICA | 0.025 mg/m3 | Not established | 0.1 mg/m3 TWA | Not established | 0.05 mg/m3 | |
| Eye/type..... | Liquid chemical goggles. | | | | | |
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. | | | | | |
| Gloves/ type..... | Chemical resistant gloves. | | | | | |
| Clothing/type..... | Wear adequate protective clothes. | | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | | |
| Other/type..... | Emergency showers and eye wash stations should be available. | | | | | |
| Ventilation requirements..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. . | | | | | |

SECTION 09: Physical and chemical properties

| | |
|--|----------------------------|
| Physical state..... | Liquid. |
| Colour..... | Beige. |
| Odour..... | Solvent odour. |
| Odour threshold (ppm)..... | Not Available. |
| Vapour pressure (mm Hg)..... | No data. |
| Vapour density (air=1)..... | >1. |
| pH..... | Not applicable. |
| Relative Density (Specific Gravity)..... | 8.39 lbs/USG - 1.0068. |
| Freezing point (deg C)..... | Not Available. |
| Solubility..... | Slightly soluble in water. |
| Boiling point (deg C)..... | 97°C. |
| Evaporation rate..... | Moderate. |
| Flash point (deg C), method..... | 4°C Closed Cup. |
| Auto ignition temperature (deg C)..... | > 500°C. |
| Upper flammable limit (% vol)..... | 6.9. |
| Lower flammable limit (% vol)..... | 1.2. |
| Coefficient of water/oil distribution..... | Not Available. |
| % Volatile by volume..... | 75%. |
| VOC..... | 1.75 lbs/USG - 209.70 g/L. |
| Viscosity..... | 1000 cps spindle # 4. |

SECTION 10: Stability and reactivity

| | |
|--|--|
| Stability..... | Stable at normal temperatures and pressures. |
| Reactivity conditions..... | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Incompatibility..... | Keep away from heat. Incompatible with strong oxidizers. |
| Hazardous products of decomposition..... | Dense black smoke. Oxides of nitrogen. Oxides of carbon (CO,CO2). |
| Hazardous polymerization..... | Hazardous polymerization will not occur. |

SECTION 11: Toxicological information

| INGREDIENTS | LC50 | LD50 |
|--------------------------------|---|--|
| ACETIC ACID, TERT-BUTYL ESTER | >2,230 mg/m3 4 hours rat | 4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal |
| TOLUENE | 8000 ppm rat inhalation 400 ppm mouse inhalation 24hr | 5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal |
| SBR (STYRENE BUTADIENE RUBBER) | No data | No data |
| HYDROCARBON POLYMER | No data | No data |
| CALCIUM CARBONATE | No data | 6450 mg/kg rat oral |
| BENTONE | No data | No data |

PRODUCT: AV 7655 ROCKER PANEL PROTECTOR BEIGE**SECTION 11: Toxicological information**

| INGREDIENTS | LC50 | LD50 |
|----------------------------------|---|--|
| TITANIUM DIOXIDE | No data | > 10,000 mg/kg rat oral > 10,000 mg/kg rabbit dermal |
| CRYSTALLINE SILICA | No data | >22,500 mg/kg oral, rat |
| Route of entry | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Can cause moderate skin irritation, defatting and dermatitis. Contact with eyes may cause irritation. | |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal . | |
| Carcinogenicity of material..... | Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. . IARC has classified Titanium Dioxide as a group 2B carcinogen. | |
| Reproductive effects..... | Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. | |

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
Biodegradability..... Not Available.

SECTION 13: Disposal considerations

Waste disposal..... Empty containers must be handled with care due to product residue. This material and its container must be disposed of as hazardous waste. Avoid release to the environment.

SECTION 14: Transport information

TDG Classification..... UN1139 - COATINGS SOLUTION - Class 3 - Packing Group II - This product meets the limited quantity exemption when packaged in containers less than 5 Litres.
DOT Classification (Road)..... UN1139 - COATINGS SOLUTION - Class 3 - Packing Group II .
IATA Classification (Air)..... UN1139 - COATINGS SOLUTION - Class 3 - Packing Group II .
IMDG Classification (Marine)..... UN1139 - COATINGS SOLUTION - Class 3 - Packing Group II - EmS: F-E S-E.
Marine Pollutant..... No.
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status..... On Domestic Substances List (DSL).
OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III
Section 302 - extremely hazardous None.
substances
Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
Section 313..... Toluene.
EPA hazardous air pollutants (HAPS) Toluene.
40CFR63
TSCA inventory status..... All components are listed.
California Proposition 65..... This product contains Toluene known to the State of California to cause (developmental) reproductive toxicity. This product contains Crystalline Silica (Quartz) known to the State of California to cause cancer. California is in the process of listing Titanium Dioxide to Proposition 65 as a known carcinogen.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS.
Telephone number:..... (800) 387-7981.
Disclaimer:..... **DISCLAIMER:** All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed

PRODUCT: AV 7655 ROCKER PANEL PROTECTOR BEIGE**SECTION 16: Other information**

Disclaimer:..... to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Preparation date: MAY 21/2015